



Introducing the New England Stormwater Retrofit Manual

National Stormwater Roundtable 2022

Jamie Houle

*Director – University of New Hampshire Stormwater
Center*

May 18th, 2022

Manual Team and Manual Funding

Presenting Today:



James Houle

*Director – University of New
Hampshire Stormwater Center*

This manual was funded by a technical assistance grant provided by the EPA's Southeast New England Program (SNEP).

<https://snepnetwork.org/stormwater-retrofit-manual/>



Nate Pacheco

Water Resources Specialist - VHB



Theresa McGovern

Water Resources Engineer - VHB



Mark Voorhees

Environmental Engineer - EPA

Additional Authors:


Technical Advisory Committee:

- CTDEEP
- EPA
- MADEP
- MassDOT
- MEDEP
- NHDES
- RIDEM
- RIDOT
- VTDEC
- UNHSWC

Southeast New England Program (SNEP) Network Context



2021 - 2025 PRIORITY ACTIONS



Goals of New England Stormwater Retrofit Manual

- Provide research-based guidance on **planning, siting, and designing** retrofit stormwater control measures (SCMS) **where regulatory requirements to not dictate prescribed specifications**
- Present an approach for **crediting pollutant and runoff volume reductions** associated with these SCMs
- Present a framework for **selecting the optimal SCM** for a specific project/site


Why this Manual Matters

- This manual fills a gap in existing retrofit guidance by...
- Encouraging designers to **move beyond prescriptive new/redevelopment mindset**
- Helping designers **piece SCM components together to arrive at the best SCM** to meet project and site-specific needs
- **Promoting the use of EPA-developed water quality crediting methods** to quantify SCM impact

Manual Highlights: Planning and Crediting

Retrofit Approach: Opportunistic Approach


- Incorporation of SCMs into already planned and needed construction projects
- Key Considerations:
 - **Be proactive in identifying opportunities.**
 - **Develop a suite of typical SCMs.**
 - **Be willing to be flexible with the project specifications**
 - **Tailor the scale and type of SCMs to the project**



Source: <https://www3.epa.gov/region1/npdes/stormwater/tools/arlington-ma-infiltration-trench-conceptual-design.pdf>


Retrofit Approach: Planning Approach

- Proactively planning retrofits and prioritizing sites
- Steps:
 1. Understand and Quantify Goals
 2. Identify Potential Sites
 3. Identify SCMs
 4. Prioritize Sites and Controls
 5. Implement SCMs




Source: <https://www.arcgis.com/apps/webappviewer/index.html?id=b516ed62a55847e28d0243ac07206856>

Crediting Approach: SCM Performance Curves



See our handout for more information on SCM Performance Curves and how to utilize them!



Sizing for Performance



Sizing Details

System	WQV ft ³ (m ³)	Actual WQV ft ³ (m ³)	% of normal design	Rain Event in (mm)	Sizing Method
SGWSC	7,577 (214.6)	720 (20.4)	10%	0.10 (2.5)	Static
IBSCS	1,336 (37.8)	310 (8.8)	23%	0.23 (5.8)	Dynamic

$$WQV = \left(\frac{P}{12} \right) \times IA$$


Dynamic Bioretention
Sizing

$$Af = Vwq * \frac{df}{(i(hf + df)tf)}$$


Static SGW System Sizing

$$Q = CdA\sqrt{2gh}$$


Oyster River Road Cumulative Distribution Frequency



Durham Bio-5 Cumulative Distribution Frequency



Water Quality Performance (RE)



System	TSS	TN	TP
Conv. Bioretention Average (4)	91%	36%	34%
Durham Bioretention (23% IBSC)	81%	27%	45%
Conv. Subsurface Gravel Wetland	96%	54%	58%
Subsurface Gravel Wetland (10% SGWSC)	75%	23%	53%

Manual Highlights: SCM Selection and Design

SCM Selection and Design: Treatment Unit Operations and Processes (UOPs)

UOPs: Unit Operations and Processes

Operations: methods of treatment in which application of *Physical* and *Hydrologic* forces dominate.

Processes: methods of treatment in which *Chemical* or *Biological* activities are involved.



Hydrologic



Physical



Chemical




Biological

Selection and Design: Linking SCMs to UOPs and Performance Curves

SCM Type	Primary UOP	Performance Curve Category
Infiltration Swale	Hydrologic: Infiltration	Infiltration Basin
Rain Garden (with underdrain)	Physical: Filtration	Bio-Filtration
Gravel Wet Vegetated Treatment System	Biological: Nitrification/ Denitrification	Gravel Wetland


SCM Guidance: Functional Components

- Determine form and function of SCM
- Can be broken down as follows:
 - Collection and Distribution
 - Pretreatment
 - Discharge



Source: MassDOT Stormwater Design Guide, 2022

SCM Guidance: Putting It All Together



Manual Highlights: Breaking through Prescriptive Guidance


Breaking Through Prescriptive Guidance: Sizing Requirements

Current Typical Requirement:


Size SCMs to meet the required WQV (typically 1 inch)

Proposed Retrofit Guidance:

Use SCM Performance Curves to size optimal cost-effective SCMs within a site



Distribution of Precipitation Events by Depth; Boston, MA 1992-2014



Precip Depth (in)	Probability %
0.05-0.2	39
0.2-0.5	66
0.5-0.8	80
0.8-1.0	85
1.0-1.5	92
1.5-2.0	95
>2.0	98

Breaking Through Prescriptive Guidance: Separation to Groundwater/Bedrock


Current Typical Requirement:

Provide 1-3 ft of separation to
ESHGWT

Proposed Retrofit Guidance:

Provide 1 ft of separation to
ESHGWT when possible (SCMs
with a filtering layer should
always provide 1 ft)

Gravel Wetland



Breaking Through Prescriptive Guidance: Flexibility for IA Disconnection Design Criteria


Current Typical Requirement:

Meet slope, length/width, contributing area, soils, vegetation, setback, and ownership criteria



Proposed Retrofit Guidance:

Provide IA Disconnection wherever possible and use the SCM performance curves to determine credit



Breaking Through Prescriptive Guidance: Pretreatment as an O+M Measure


Current Typical Requirement:

Prescribed pretreatment
measure types and sizing
criteria

Proposed Retrofit Guidance:

Provide pretreatment whenever
possible

Leaching Basin



In Summary...

- Be creative in retrofit scenarios!
- Some treatment (even small!) is better than none at all
- The SCM Performance Curves are powerful tools for sizing and crediting SCMs
- Construct an SCM that works best for your site/project
- Don't be constrained!

Acknowledgments

- EPA and SNEP Network
- Elizabeth Scott
- Kimberly Groff
- TAC
 - Tom Ballestero – UNHSWC
 - Henry Barbaro – MassDOT
 - Eric Beck – RIDEM
 - Ian Dombrowski - EPA
 - Kathleen Knight – CTDEEP
 - Daniel Macadam – UNHSWC
 - Tom Maguire – MADEP
 - Padraic Monks – VT
 - Brian Moore - MassDOT
 - Nick Pisani – RIDEM
 - Cody Ray – EPA
 - Matthew Reardon – MADEP
 - Alisa Richardson – RIDOT
 - Michael Sadler – VT
 - Laura Schiffman – MADEP
 - Newt Tedder – EPA

Additional Content

Why a retrofit manual

Historic Municipal WaterWorks,
Dover, NH












Why a retrofit manual

Historic Municipal Water Works

Dover, NH



Where did the idea of a manual come from?



Watershed Approach

Location	Best Management Practice	Rationale
Along west side of Jamaica Way	Tree Filters (5)	Existing storm drain line and several catch basins. There are also some recently planted trees that could be transplanted into tree filter units. These would provide some treatment through filtration, infiltration, rhizosphere, and flow attenuation. Media amendments would be added to remove phosphorus.
Halifax St and Pondview Ave	Tree Filters (2)	There is an existing storm drain line and catch basins on each side of the Halifax St. The existing street scape includes trees.
Halifax St near S. Huntington St	Tree Filter	There is an existing storm drain line and a catch basin that could be converted to a tree filter.
<ul style="list-style-type: none"> • Parkwood Terrace and Jamaica Way • Perkins St and Jamaica Way 	Media Box Filters	Existing storm drain line and catch basin. Large vegetated strip between road and sidewalk that is likely in City right-of-way. Large trees are in this proximity so an MBF would be a better fit.
<ul style="list-style-type: none"> • North end of Parkton Rd • Perkins St and S. Huntington • Castleton St • Evergreen St and S. Huntington 	Media Box Filters	Existing storm drain line and catch basins on each side of Perkins St. No vegetated area but an MBF might fit under the road depending on other utilities.
Just south of Highland Rd and Jamaica Way intersection	Bioretention	Existing storm drain line and room for a bioretention cell that could treat surface runoff and then be piped into existing line.
West of Jamaica Way near Wards Pond	Bioretention	Plenty of area for a bioretention cell but some trees may need to be removed. Effluent could discharge cool treated water to Wards Pond.
<ul style="list-style-type: none"> • El Mundo Newspaper • Intersection of Bynner St and South Huntington • Intersection of Evergreen St and South Huntington 	Green Roof and Rain Barrel installations	These are flat roof buildings with concrete block or brick exteriors, which may be strong enough for green roof systems. There are several other buildings in the drainage area that could be identified if this is a viable strategy.
<ul style="list-style-type: none"> • MSPCA, Animal Care & Adoption Center • Perkins Square – Sagamore Advisors • Mt. Pleasant Home 	Tree Filters, Bioretention(s), media box filters	Three of the largest, privately owned impervious cover areas in the watershed. There are media strips, large parking areas, and large roof tops that could all be managed using various GI strategies.



And then reality



"Hi, Tim and I were just chatting about siting systems. Is there any reason why we could not put a system where the orange oval is in the pic below?"

"I'm going to say almost definitively no. It's private property and we have no way to get those property owners to work with us. Additionally, my understanding is that we want a visible area for public education (a park in this tributary area). "

Other Considerations




In the "TOPOGRAPHY" layer there are several sub-layers that seem to be paired for identical points on the map. They consistently differ by 6.5'. Which surface elevation layer is correct or relative to the Pipe Invert Elevation layers? For example:

Sub-Layer Name	Elevation	Elevation	Elevation	General Location of Point
Topo DETBCB Elevation	29.0	34.8	28.3	East of Jamaica Way / Willow Pond Rd intersection.
Topo DET Elevation	22.5	28.3	21.8	Same as above
Difference	6.5	6.5	6.5	
Topo INDBCB Elevation	26.5			On contour line southeast of Jamaica Way / Willow Pond Rd. int.
Topo INDD Elevation	20			Same as above
Difference	6.5			
Topo BCB Elevation	33.0	31.8	34.2	In vicinity of Jamaica Way / Willow Pond Rd. intersection
TOP GEN Elevation	26.5	25.3	27.7	Same as above
Difference	6.5	6.5	6.5	

Why a retrofit manual




Why a retrofit manual



Infiltration Trench (IR = 1.02 in/hr) BMP Performance Table: Long-Term Phosphorus Load Reduction								
BMP Capacity: Depth of Runoff Treated from Impervious Area (inches)	0.1	0.2	0.4	0.6	0.8	1.0	1.5	2
Runoff Volume Reduction	26.3%	44.6%	68.2%	81.0%	88.0%	92.1%	96.5%	98.
Cumulative Phosphorus Load Reduction	27%	47%	73%	86%	92%	96%	99%	10

Figure 3- 4: BMP Performance Curve: Infiltration Trench (infiltration rate = 1.02 in/hr)




Stormwater Management Design - 70.5 acre Ultra-Urban Drainage Area			
Sizing Comparison of Capital Costs and Relative Phosphorus Load Removal Efficiency			
Best Management Practice Size	Depth of Runoff Treated from Impervious Area (in)	*Storage Volume Cost (\$/ft³)	**Total Phosphorus Removal Efficiency (%)
Subsurface Gravel Filter - Minimum Size	0.35	\$1,016,912	62%
Subsurface Gravel Filter - Moderate Size	0.5	\$1,452,732	80%
Subsurface Gravel Filter - Full Size	1.0	\$2,905,463	96%
*Storage Volume Cost estimates provided by EPA-Region 1 for Opti-Tool methodology, 2015-Draft			
**Total Phosphorus %RE based on Appendix F Massachusetts MS4 Permit			

What can the manual do for me

Chapter 2 – Retrofit Approach: This chapter defines what a retrofit is and discusses the approaches to identifying and implementing SCMs in a retrofit situation. It reviews the opportunistic approach (including measures as part of other efforts) and the planning approach (proactive planning and prioritization).


Retrofit Approach: Planning Approach

- Proactively planning retrofits and prioritizing sites
- Steps:
 1. Understand and Quantify Goals
 2. Identify Potential Sites
 3. Identify SCMs
 4. Prioritize Sites and Controls
 5. Implement SCMs



Source: <https://www.arcgis.com/apps/webappviewer/index.html?id=b516ed62a55847e28d0243ac07206856>


Planning Approach:





Courtesy of Wayne Chouinard, Arlington DPW





Courtesy of Wayne Chouinard, Arlington DPW

Chapter 3 – Credits: This chapter discusses credits, or the quantification of a SCM's stormwater benefits. It explains the need for credits and presents the SCM Water Quality Treatment Performance Curves, a crediting scheme that is becoming widely accepted in New England for quantifying benefits. The credits show that small scale controls that do not necessarily meet widely implemented sizing standards can still provide significant benefit.

Table 1. Modeled costs and Infiltration trench performance*

Unit	Cost (\$)
System	2,200
IC treated per acre (per ha)	18,857 (44,000)
TP per lb (per kg)	24,750 (55,000)
TN per lb (per kg)	3,930 (8,609)
TSS per lb (per kg)	86 (190)
Volume eliminated per cf (per m ³)	0.11 (4)

Other Benefits



DA = 10.47 acres
IC = 3.14 acres
DSV = 1,200 cf
PSC = 0.11



The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to UNHSC without delay. The Copyrights to all designs and drawings are the property of UNHSC. Reproducing or use for any purpose other than that authorized by UNHSC is forbidden.



University of New Hampshire
35 Colovos Road
Durham, NH 03824
Phone (603) 862-2818
Fax (603) 862-3957
<http://www.unh.edu/unhsc>

No.	Date	Revision
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		
61		
62		
63		
64		
65		
66		
67		
68		
69		
70		
71		
72		
73		
74		
75		
76		
77		
78		
79		
80		
81		
82		
83		
84		
85		
86		
87		
88		
89		
90		
91		
92		
93		
94		
95		
96		
97		
98		
99		
100		
101		
102		
103		
104		
105		
106		
107		
108		
109		
110		
111		
112		
113		
114		
115		
116		
117		
118		
119		
120		
121		
122		
123		
124		
125		
126		
127		
128		
129		
130		
131		
132		
133		
134		
135		
136		
137		
138		
139		
140		
141		
142		
143		
144		
145		
146		
147		
148		
149		
150		
151		
152		
153		
154		
155		
156		
157		
158		
159		
160		
161		
162		
163		
164		
165		
166		
167		
168		
169		
170		
171		
172		
173		
174		
175		
176		
177		
178		
179		
180		
181		
182		
183		
184		
185		
186		
187		
188		
189		
190		
191		
192		
193		
194		
195		
196		
197		
198		
199		
200		
201		
202		
203		
204		
205		
206		
207		
208		
209		
210		
211		
212		
213		
214		
215		
216		
217		
218		
219		
220		
221		
222		
223		
224		
225		
226		
227		
228		
229		
230		
231		
232		
233		
234		
235		
236		
237		
238		
239		
240		
241		
242		
243		
244		
245		
246		
247		
248		
249		
250		
251		
252		
253		
254		
255		
256		
257		
258		
259		
260		
261		
262		
263		
264		
265		
266		
267		
268		
269		
270		
271		
272		
273		
274		
275		
276		
277		
278		
279		
280		
281		
282		
283		
284		
285		
286		
287		
288		
289		
290		
291		
292		
293		
294		
295		
296		
297		
298		
299		
300		
301		
302		
303		
304		
305		
306		
307		
308		
309		
310		
311		
312		
313		
314		
315		
316		
317		
318		
319		
320		
321		
322		
323		
324		
325		
326		
327		
328		
329		
330		
331		
332		
333		
334		
335		
336		
337		
338		
339		
340		
341		
342		
343		
344		
345		
346		
347		
348		
349		
350		
351		
352		
353		
354		
355		
356		
357		
358		
359		
360		
361		
362		
363		
364		
365		
366		
367		
368		
369		
370		
371		
372		
373		
374		
375		
376		
377		
378		
379		
380		
381		
382		
383		
384		
385		
386		
387		
388		
389		
390		
391		
392		
393		
394		
395		
396		
397		
398		
399		
400		
401		
402		
403		
404		
405		
406		
407		
408		
409		
410		
411		
412		
413		
414		
415		
416		
417		
418		
419		
420		
421		
422		
423		
424		
425		
426		
427		
428		
429		
430		
431		
432		
433		
434		
435		
436		
437		
438		
439		
440		
441		
442		
443		
444		
445		
446		
447		
448		
449		
450		
451		
452		
453		
454		
455		
456		
457		
458		
459		
460		
461		
462		
463		
464		
465		
466		
467		
468		
469		
470		
471		
472		
473		
474		
475		
476		
477		
478		
479		
480		
481		
482		
483		
484		
485		
486		
487		
488		
489		
490		
491		
492		
493		
494		
495		
496		
497		
498		
499		
500		
501		
502		
503		
504		
505		
506		
507		
508		
509		
510		
511		
512		
513		
514		
515		
516		
517		
518		
519		
520		
521		
522		
523		
524		
525		
526		
527		
528		
529		
530		
531		
532		
533		
534		
535		
536		
537		
538		
539		
540		
541		
542		
543		
544		
545		
546		
547		
548		
549		
550		
551		
552		
553		
554		
555		
556		
557		
558		
559		
560		
561		
562		
563		
564		
565		
566		
567		
568		
569		
570		
571		
572		
573		
574		
575		
576		
577		
578		
579		
580		
581		
582		
583		
584		
585		
586		
587		
588		
589		
590		
591		
592		
593		







How it looks then and now



Chapter 4 – Stormwater Control Measures Selection: This chapter steps through typical unit operations and processes utilized by SCMs. This chapter also provides information on the selection and design process for SCMs and provides sizing guidance. Additional Tools/Resources for SCM selection and sizing are also provided in this chapter.

Chapter 5- Stormwater Control Measure Guidance – This chapter steps through the functional components and treatment categories used to construct a SCM. It also steps through SCM variations within each treatment category and provides information on design considerations and Operations and Maintenance (O&M) activities for each variation.

Output	Intermediate Calculation 5	Design Storage Volume	DSV	cf	1,200
		Impervious to Pervious Ratio <i>[range of 0.014 - 8]</i>	IA/PC	ac/ac	N/A
		Physical Storage Capacity: Depth of Runoff from IA <i>[range of 0 - 2, goal > 0.1, optimal 0.4]</i>	PSC	in	0.11
		PSC Notes			DSV small, increase for optimal range $0.3 \leq PSC \leq 0.6$
	Performance Curve Removal Efficiencies	Removal Efficiency: Volume	Vol _{RE}	-	0%
		Removal Efficiency: P	P _{RE}	-	20%
		Removal Efficiency: N	N _{RE}	-	23%
		Removal Efficiency: TSS	TSS _{RE}	-	49%
		Removal Efficiency: Zn	Zn _{RE}	-	59%
		Removal Efficiency: Bacteria	FIB _{RE}	-	32%
	Loading Rate	Load: Volume	Vol _{LER}	Mgal/yr	3.29
		Load: P	P _{LER}	lb/yr	6.2
		Load: N	N _{LER}	lb/yr	44.3
		Load: TSS	TSS _{LER}	lb/yr	1,378
		Load: Bacteria	FIB _{LER}	Billion MPN/yr	20
	Reductions	Reduction: Volume	Vol _{Red}	Mgal/yr	0.00
		Reduction: P	P _{Red}	lb/yr	1.2
		Reduction: N	N _{Red}	lb/yr	10.1
		Reduction: TSS	TSS _{Red}	lb/yr	682
		Reduction: Bacteria	FIB _{Red}	%/yr	32%
	Costs	Estimated Total Costs		\$	\$22,000
		Removal Costs: Volume		\$/Mgal-yr	N/A
		Removal Costs: P		\$/lb-yr	\$17,940
		Removal Costs: N		\$/lb-yr	\$2,170
		Removal Costs: TSS		\$/lb-yr	\$30
		Removal Costs: Bacteria		\$/%-yr	\$700
	O&M	Estimated O&M Hours		hr/yr	68

Other Important Components – Appendix A



Sizing Requirements

Proposed Retrofit Guidance: New site developments should fully size SCMs. Size retrofit SCMs within existing developed landscapes using the Performance Curves to optimize cost-effective pollutant reduction and encourage the installation of SCMs distributed across the landscape where runoff is generated.

Bedrock and Groundwater Separation for Infiltration SCMs

Proposed Retrofit Guidance: Infiltration systems that include a filtering layer, must have one foot or more of separation from the bottom of the filter course to the SHWT at all times. Can include the filter layer in the groundwater separation calculation.


Soils for Infiltration SCMs

Proposed Retrofit Guidance: Consider infiltration SCMs for all soil groups where infiltration is appropriate.

Pretreatment

Proposed Retrofit Guidance: Provide pretreatment whenever possible. The goal is a viable and accessible maintenance access point.





 James.Houle@unh.edu

 npacheco@vhb.com